

Market Release Note

MRN-TS9100-722-B41

Product number: TS9100, TS9120, TS9120VM

Product description: Forcefield

Product version: TS9100 7.2.2 Build 41

Release date: 16 October 2018

Interlogix is pleased to announce the availability of Forcefield 7.2.2 Build 41. This release offers a number of resolved issues.

Resolved Issues

- Resolved issues with V6 menu being corrupted. This update will both repair the corrupted menu if it is currently present, and prevent the menu from being corrupted when selected
- Resolved issue where dial up modem does not initiate a call when the download button is pressed
- User download now includes names for all users when connected to a Challenger 10 panel without memory expansion. Previously, only users 1 – 2000 would have names downloaded, this will now be any of the 2000 users which are downloaded to the Challenger10's memory
- User import file from previous versions of Forcefield now imports correctly
- Resolved issue where user image would not always show correctly on user form when a new image was uploaded
- Resolved issue where installation could fail in certain conditions related to using USB devices
- Resolved issue where mirroring could fail when used on unstable network connections
- Resolved issue where trying to delete a user could fail when using the User import file
- Resolved issue where upgrade would fail in certain conditions
- Resolved issue where security password was not being saved on the comms path

Documentation

Marketing Collateral	Forcefield datasheet
	Tecom compatibility matrix
	TruVision video plugin datasheet
	Genetec video plugin datasheet
Technical Manuals	Forcefield Installation and Setup Manual *
	Forcefield Operators Manual *
	Forcefield External Interfaces Manual *
	Forcefield Licence Form
Software downloads	Visit www.interlogix.com.au/downloads to download the latest software and firmware versions.

* May need secure login to access via Interlogix Support Portal

Known issues

- Serial printing to a third party system sometimes stops working when the system is under heavy load. As a result, occasionally the server will need to be restarted to resume functionality.
- USB keyboard and mouse must be connected on startup, otherwise they will not be detected.